



Lever Hoist POWERTEX PLH-S1

Product information

POWERTEX



Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction.
- Durable all steel construction with powder coated finish and plated frame components.
- Safe, well covered automatic load reaction brake.
- European made COROLIM[®] protected load chain.
- Corrosion resistance of the chain is equivalent to ISO944-9 C5High / ISO9223 C3
- Bottom hook with ball bearing.
- RFID equipped (chip) for easy service and inspection.
- QR code for on-site access to Multilanguage user manuals.
- User manuals in 14 languages included.
- Testcertificate enclosed.

Marking: According to standard

Temperature range: -10°C up to +50°C.

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Part Code	WLL ton	Lifting height m	Number of falls	A mm	B mm	C mm	D mm	E mm	H min mm	Ø mm	Weight kg	Delivery time
16.20PLH0025030	0.25	3	1	100	71	86	158	20	280	18	2.3	1
16.20PLH0025015	0.25	1.5	1	100	71	86	158	20	280	18	2.3	1
16.20PLH0025010	0.25	1	-	-	-	-	-	-	-	-	-	1
16.20PLH0050030	0.5	3	1	150	90	118	253	22	280	20	5.3	1
16.20PLH0050015	0.5	1.5	1	150	90	118	253	22	280	20	5.3	1
16.20PLH0100030	1	3	1	156	95	138	278	26	330	25	8.1	1
16.20PLH0100015	1	1.5	1	156	95	138	278	25	330	26	8.1	1
16.20PLH0150030	1.5	3	1	186	112	145	378	29	385	30	11.2	1
16.20PLH0150015	1.5	1.5	1	186	112	145	378	29	385	30	11.2	1
16.20PLH0300030	3	3	1	208	120	198	388	37	435	36	20.5	1
16.20PLH0300015	3	1.5	1	208	120	198	388	37	435	36	20.5	1
16.20PLH0600030	6	3	2	208	120	230	388	43	615	43	29.5	1
16.20PLH0600015	6	1.5	2	208	120	230	388	43	615	43	29.5	1
16.20PLH0600050	6	5	-	-	-	-	-	-	-	-	-	1
16.20PLH0900030	9	3	3	208	120	338	388	50	690	87	49	1
16.20PLH0900015	9	1.5	3	208	120	338	388	50	690	87	49	1

Blueprint

